

XELON LL 5W-30

Description/Application/Properties

Xelon LL 5W-30 is a modern high performance motor oil having a lowered ash content. It is formulated in particular according the requirements of VW, concerning the universal usage. Concomitantly it meets the requirements of a Low SAPs oil and thus it may be used in diesel vehicles with diesel particulate filter (DPF).

Xelon LL 5W-30 has got a performance which is expressed by the ACEA sequence C3. It assures outstanding wear protection and due to its stable performance level it provides preconditions for extended oil drain intervals (VW LongLife-service). Furthermore it demonstrably contributes to fuel economy and by this means it cares for the environments in many respects.

Specification/Recommendation

ACEA C3
MB 229.51

VW 504 00 / 507 00
BMW Longlife-04

Technical product data	Unit	Value	Method
Density at 15°C	kg/m ³	848	DIN 51 757
Viscosity at 40°C	mm ² /s	71,8	DIN 51 562
Viscosity at 100°C	mm ² /s	11,8	DIN 51 562
Viscosity Index		162	DIN ISO 2909
CCS at -30 °C	mPa.s	6200	DIN 51 377
Pourpoint	°C	-45	DIN ISO 3016
Flashpoint	°C	236	DIN ISO 2592
TBN	mg KOH/g	6,1	DIN ISO 3771