



## XELON PC Extra Synth 10W-40

**Description/Application/Properties** 

**Xelon PC Extra Synth 10W-40** is a semi-synthetic low friction oil to be used in passenger cars gasoline and diesel engines. It is produced by blending high quality synthetic components and mineral base stocks and additives of most progressive technology. Suitable also under severe operating conditions in modern passenger car engines, turbo- or non-turbo charged.

**Xelon PC Extra Synth 10W-40** by its optimized formulation provides lowered fuel- and oil consumption. Because of its extended viscosity range the all seasons use is possible. The dispersing power, expressed by the performance level of this product, prevents deposits and pluggings in the oil circuit and thus keeps the engine clean. Modern oxidation inhibitors extend the service life of the oil and the optimal wear protection cares for long engine life.

## Specification/Recommendation

| ACEA A3 / B4   | VW 505 00 |
|----------------|-----------|
| API SL / ĆF    | MB 229.1  |
| Renault RN 700 |           |
| PSA B71 2296   |           |

| Technical product data | Unit     | Value | Method       |
|------------------------|----------|-------|--------------|
| Density at 15°C        | kg/m³    | 861   | DIN 51 757   |
| Viscosity at 40°C      | mm²/s    | 97,1  | DIN 51 562   |
| Viscosity at 100°C     | mm²/s    | 14,7  | DIN 51 562   |
| Viscosity Index        |          | 158   | DIN ISO 2909 |
| CCS at -25 °C          | mPa.s    | 5310  | DIN 51 377   |
| Pourpoint              | °C       | -42   | DIN ISO 3016 |
| Flashpoint             | °C       | 230   | DIN ISO 2592 |
| TBN                    | mg KOH/g | 8,8   | DIN ISO 3771 |