

XELON PC Extra Synth 5W-30

Description/Application/Properties

Xelon PC Extra Synth 5W-30 is a low friction oil for all passenger car gasoline- and diesel-engines. It is exclusively made from high quality Polyalphaolefines (PAO), which are combined with additives of the most progressive technology.

Xelon PC Extra Synth 5W-30 provides reduced oil- and fuel-consumption because of its optimized formulation. Excellent dispersancy prevents deposits und pluggings in the oil circuit and thus keeps the motor clean. Outstanding low-temperature properties enable smooth cold start and quick oiling of the engine, even at frost. Modern oxidation inhibitors ncrease the service life of the oil and the assured wear protection are best conditions for a long motor life.

Xelon PC Extra Synth 5W-30 is outstandingly applicable at all operation conditions (highway, city traffic, s.a.o.) in modern passenger car engines, wether turbo charged or not.

Specification/Recommendation

ACEA A3/B4
API SL

Technical product data	Unit	Value	Method
Density at 15°C	kg/m ³	849	DIN 51 757
Viscosity at 40°C	mm ² /s	62,0	DIN 51 562
Viscosity at 100°C	mm ² /s	11,1	DIN 51 562
Viscosity Index		168	DIN ISO 2909
CCS at -30 °C	mPa.s	4420	DIN 51 377
Pourpoint	°C	-42	DIN ISO 3016
Flashpoint	°C	228	DIN ISO 2592
TBN	mg KOH/g	8,5	DIN ISO 3771